

Sayı: 17812098-TİM.AKİB.GSK.UYG.2023/1382-5019
Konu: ETSG Sektör Duyurusu

Mersin, 24/10/2023

Sayın Üyemiz,

Türkiye İhracatçılar Meclisinden alınan 24.10.2023 tarihli yazıda; sanayicilerin ihtiyaç duyduğu hammadde ve yarı mamul niteliğindeki sanayi ürünlerine ilişkin her yıl 1 Ocak ve 1 Temmuz tarihlerinde yürürlüğe girecek şekilde yapılan askıya almanın, üretimin tüketimi karşılamayan ürünlere ise kota başvurularının, ülkemiz temsilcilerinin de yer aldığı toplantılarda Avrupa Komisyonu tarafından müzakere edilerek karara bağlandığı ifade edilmektedir.

Anılan yazıda devamla, AB ya da Türk firmalarınca 01/07/2024 tarihinden itibaren gümrük vergilerinin askıya alınması veya tarife kontenjanı uygulanması talep edilen eşyaya ilişkin itirazların Ticaret Bakanlığına en geç 06/11/2023 tarihine kadar intikal ettirilmesi gerektiği belirtilmekte olup, söz konusu liste ekte yer almaktadır.

Bununla birlikte, başvuruların işleme konulabilmesi için en geç yukarıda belirtilen tarihe kadar Ticaret Bakanlığından evrak kayıt numarası alınmış olması gerektiği bildirilmekte olup, itirazlara ilişkin formlara aşağıda yer alan adresten ulaşılabilmektedir.

Öte yandan, askıya alma sistemine ilişkin detaylı bilgi için 2023/18 sayılı İthalat Tebliği'nin incelenebileceği veya aşağıda paylaşılan Bakanlık yetkilileri ile iletişime geçilebileceği; ayrıca, firmalar tarafından listede yer alan ürünlerin özel tanımlı olmasından dolayı, GTİP'den ziyade ürün tanımlarının incelenerek tanımı karşılayacak üretimin bulunması durumunda başvuru yapılmasının önem arz ettiği belirtilmektedir.

Bilgilerini rica ederim.

H. Okan ŞENEL
Genel Sekreter Yrd.

Ek: İtirazlara İlişkin Form Adresi (<https://www.ticaret.gov.tr/ithalat/askiya-alma-ve-tarife-kontenjani/askiya-alma-sistemi>) ve Liste (54 sayfa)

Sayı: 17812098-TİM.AKİB.GSK.UYG.2023/1382-5019
Konu: ETSG Sektör Duyurusu

Mersin, 24/10/2023

İletişim Bilgileri			
Hammadde ve Ara Mamul Sektörleri			
Ad-Soyad	Unvan	Telefon	Mail
Özge SEZGİN	Uzman	0312 204 99 25	sezgino@ticaret.gov.tr
Koray ÇINAR	Uzman	0312 204 99 33	cinark@ticaret.gov.tr
Mehmet BARAN	Uzman Yrd.	0312 204 95 81	M.Baran2@ticaret.gov.tr
Elektronik ve Makina Sektörleri			
Ad-Soyad	Unvan	Telefon	Mail
Serkan ULUYOL	Uzman	0312 204 95 76	uluyols@ticaret.gov.tr
Tuba KÖSE SANDALCI	Uzman	0312 204 99 30	sandalcit@ticaret.gov.tr

CYCLE 2024-07

Changes in relation to the previous version: Two working numbers (1111 and 1112) with chemical substances were omitted and are now added at the top of the new suspensions list.

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Working Number	Description	Quotas	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
2905 29 90		6578062/2023	1033	Prop-2-in-1-ol (propargil alcohol) (CAS RN 107-19-7) with a purity by weight of 99 % or more	Q/75tonnes, 01.07-31.12	New	UNDER EXAMINATION	ES	Applicant	Round 2024/7 raw material in the manufacture of the different salts that manufactures as APIs.
8482 99 00		6609224/2023	1044	Punched cages of various diameters, - made of flat rolled steel, - with tensile strength of 270 MPa or more, for the production of tapered roller bearings (2)	Q/4000000pieces, 01.07-31.12	New	UNDER EXAMINATION	DE	Applicant	Round 2024/7 used for the manufacture of tapered roller bearings.
8482 99 00		6391321/2023	1017	Molded precision cages, male part, including rivet, and female part, of diameters min 15 mm and max 140 mm,	Q/647tonnes, 01.07-31.12	New	UNDER EXAMINATION	IT	Applicant	Round 2024/7 used in multiple applications like industrial &

				used for manufacturing radial ball bearings (2)						automotive electrical motors, machinery axles, industrial applications, bikes, skates.
ex 3913 90 00	87	167201/2010	0710I	Sodium hyaluronate, non sterile, with: - a weight average molecular weight (M _w) of not more than 900 000, - an endotoxin level of not more than 0,008 Endotoxin units (EU)/mg, - an ethanol content of not more than 1 % by weight, - an isopropanol content of not more than 0,5 % by weight	Q/500kilograms, 01.01-31.12	Amendment	UNDER EXAMINATION	BE	Applicant	Round 2024-07 - request for increase the quota amount, from currently 300 kg to 500 kg per year. //
ex 8482 99 00	60	4921841/2020	0700	Inner or outer rings made of steel, not hardened or not grinded, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of: - 14 mm or more but not more than 77 mm for the inner ring, - 26 mm or more but not more than 101 mm for the outer ring, for use in the manufacture of bearings (2)	Q/9000000kilograms, 01.07-31.12	Amendment	UNDER EXAMINATION	PT EU TR TR TR	Applicant Opposed Opposed Opposed Opposed	Round 2024-07 - Objection. Set with quota period 1.1-30.6. in the proposal for amendment of Reg. 2021/2283. It is placed under the amendments for the historical background. Round 2024-01- Review of the quota.// OBJECTION from TR. Objection accepted, small decrease of quota amount.
ex 8501 31 00	80	2059389/2022	0712	DE(15.09.2023) request for amendment: Power transmission device for controlling the output of exhaust gas turbochargers, consisting of:	Q/650000pieces, 01.01-31.12	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2024-01 request for amendment: Electronic actuator: component for control of turbo compressors

				<ul style="list-style-type: none">- a DC motor of an output not exceeding 600 W,- for usage with a supply voltage of 8 V to 48 V,- with motor connection (plug-in connection),- whether or not with position sensor,- whether or not with integrated control and power electronics,- whether or not with spring mechanism for resetting the lever,- built in a housing with reduction gear and lever attached to the motor drive shaft, or- built in a housing with threads integrated into the rotor of the motor for linear movement of the integrated control rod <p>---</p> <p>Current text: Electronic actuator consisting of:</p> <ul style="list-style-type: none">- a DC motor having a power of less than 600 W,- for usage with a supply voltage of 12 V to 48 V,- with motor connection (plug-in connection),- with contactless position sensor,- built in a rectangular housing of a width of less than 100 mm and a length of less than 150 mm, with reduction gear and lever attached to the motor drive shaft or- in a cylindrical housing of a length off less than 150mm and with a diameter of less than 100 mm, with threads integrated into the rotor of the motor for linear movement of the integrated control rod						of the kind used in motor vehicles
--	--	--	--	---	--	--	--	--	--	------------------------------------

ex 8501 40 20 ex 8501 40 80	65 60	1037/2007	0711	<p>DE(12.09.2023) request for amendment: Electric AC motor, single-phase, whether or not with commutator</p> <ul style="list-style-type: none">- with a nominal output of 180 W or more,- with an input power of 150 W or more but not more than 2 700 W,- with an external diameter of more than 45 (± 0,2 mm) but not more than 135 mm (± 0,2 mm),- with a rated speed of more than 10 000 rpm but not more than 50 000 rpm,- whether or not equipped with air-inducting ventilator,- whether or not with mechanical device (pinion, screws, gear connection etc.) on the shaft, <p>for use in the manufacture of domestic appliances (2)</p> <p>---</p> <p>Current request: Electric AC motor, single-phase, whether or not with commutator</p> <ul style="list-style-type: none">- with a nominal output of 180 W or more,- with an input power of 150 W or more but not more than 2 700 W,- with an external diameter of more than 120 mm (± 0,2 mm) but not more than 135 mm (± 0,2 mm),- with a rated speed of more than 10 000 rpm but not more than 50 000 rpm,- whether or not equipped with air-inducting ventilator,- whether or not with mechanical device (pinion, screws, gear connection etc.) on the shaft,	Q/1000000pieces, 01.07-31.12	Amendment	UNDER EXAMINATION	DE	Applicant	Round 2024-07 - request for amendment. //
--------------------------------	----------	-----------	------	--	------------------------------	-----------	-------------------	----	-----------	---

2920 90 10		6580292/2023	1035B	1,3,2-Dioxathiolane 2,2-dioxide (CAS RN 1072-53-3) with a purity by weight of 99,5 %, or more	S	New	UNDER EXAMINATION	HU	Applicant	Round 2024/7: Raw material to be mixed with other raw materials, used in a technological system for the production of electrolyte for lithium-ion batteries .
2924 29 70		6325327/2023	1016	-Butyl ((1-aminocyclohexyl)methyl) carbamate acetate with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2024/7 used as pharmaceutical ingredient
2929 90 00		6223040/2023	1006	(2S)-2-[[2-[2-[2-[2-[2-[2-[2-(2-Azidoethoxy)ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethoxy]ethylamino]-2-oxoethoxy]acetyl]amino]-N-[4-(hydroxymethyl)phenyl]-6-[[4-methoxyphenyl]-diphenylmethyl]amino]hexanamide (CAS RN 1224601-12-0) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2024/7 used to manufacture a new Active Pharmaceutical Ingredient.
2931 90 00		6603965/2023	1043	4-Phenoxybenzeneboronic acid (CAS RN 51067-38-0) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	FR	Applicant	Round 2024/7 used in the making of pharma.
2931 90 00		6579872/2023	1034	Trimethylindium (CAS RN 3385-78-2) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION	NL	Applicant	Round 2024/7 Precursor for metallic gallium in highly sophisticated technological processes
2932 19 00		6256630/2023	1010	2-Methylfuran (CAS RN 534-22-5) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	BE	Applicant	2024/7 -used mainly as raw material for pharma
2932 19 00		6180825/2023	1004	(2S,3S,4S,5R)-3-(3,4-Difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl)tetrahydrofuran-2-yl-4-nitrobenzoate (CAS RN 2875066-49-0) with a purity by weight of 97 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2024/7 used for the manufacture of a new active ingredient.

2933 39 99		6471196/2023	1019	Tert-butyl N-[5-(trifluoromethyl)pyridin-3-yl]carbamate (CAS RN 1187055-61-3) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 2024/7 raw material for the production of an intermediate.
ex 2933 39 99	90	6612455/2023	1954	(2 <i>S</i> ,4 <i>S</i>)-4-Ethoxy-2-[4-(methoxycarbonyl)phenyl]piperidin-1-ium(2 <i>Z</i>)-3-carboxyprop-2-enoate with a purity by weight of 98,0 % or more	S	New	UNDER EXAMINATION	SI	Applicant	Round 2024/07 used for pharma
2933 59 95		6223117/2023	1007	(1 <i>R</i> ,5 <i>S</i>)-8-Benzyl-3,8-diazabicyclo[3.2.1]octane;4-(4-hydroxyphenyl)phenol (2:1) (CAS RN 2642049-87-2) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2024/7 used to manufacture a new Active Pharmaceutical Ingredient.
2933 99 80		6580773/2023	1037	2-[6-Methyl-2-(4-methylphenyl)imidazo[1,2- <i>a</i>]pyridin-3-yl]acetic acid (zolpidic acid) (CAS RN 189005-44-5) purity by weight of 98 % or more	S	New	UNDER EXAMINATION	CZ	Applicant	Round 2024/7 used as an intermediate for manufacturing the pharmaceutical drug substance.
2934 99 90		6580649/2023	1036	2-Chlorothioxanthen-9-one (CAS RN 86-39-5) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	CZ	Applicant	Round 2024/7 used as an intermediate for manufacturing the pharmaceutical.
2934 99 90		6025558/2023	1000	Vutrisiran (INN) (CAS RN 1867157-35-4) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	SI	Applicant	2024/7 raw material used in the development and is one of the ingredients used.
2934 99 90		6518181/2023	1029	1-(Tetrahydro-2 <i>H</i> -pyran-2-yl)-5-(4,4,5,5-tetramethyl-1,3,2-dioxaborolan-2-yl)-1 <i>H</i> -pyrazole (CAS RN 903550-26-5) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	IT	Applicant	Round 2024/7 used for production of pharmaceuticals
2935 90 90		6181874/2023	1005	Sodium;[4-chloro-7-[2-[(1 <i>S</i>)-2-(3,5-difluorophenyl)-1-[[2-[(2 <i>S</i> ,4 <i>R</i>)-5,5-difluoro-9-(trifluoromethyl)-7,8-diazatricyclo[4.3.0.0 ^{2,4}]nona-1(6),8-	S	New	UNDER EXAMINATION	ES	Applicant	Round 2024/7 used in the manufacturing of a new Pharmaceutical intermediate.

				dien-7-yl]acetyl]amino]ethyl]-6-(3-methyl-3-methylsulfonylbut-1-ynyl)pyridin-3-yl]-1-(2,2,2-trifluoroethyl)indazol-3-yl]-methylsulfonylazanide (Lenacapavir sodium) (CAS RN 2283356-12-5) with a purity by weight of 98 % or more						
2942 00 00		6223253/2023	1009	Dimethylamine—borane (1:1) (CAS RN 74-94-2) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION	ES	Applicant	Round 2024/7 used for the manufacture of intermediates for the production of pharmaceuticals.
3204 15 00		6790688/2023	1052	Indigo Vat 40 % Solution, Vat Blue 1 reduced (CAS RN 835912-68-0), Na-/K-Salt (CAS RN 894-86-0) (Mix 3:2) 40 % (CAS RN 207692-02-2); Napthalenesulfonic acid (CAS RN 9084-06-4) 0,5 %; Potassium hydroxide (CAS RN 1310-58-3) polymer with formaldehyde, sodium salt 2,4 %; Sodium hydroxide (FKS) (CAS RN 1310-73-2) 1,6 %; Water (CAS RN 7732-18-5) 55,5 %	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/7 Used in Textile Industry for dyeing textile products.
3204 17 00		6697748/2023	1053	Colorant C.I. Pigment Yellow 12 (CAS RN 6358-85-6) and preparations based thereon with a colorant C.I. Pigment Yellow 12 content of 21 % or more by weight	S	New	UNDER EXAMINATION	IE	Applicant	Round 2024/7 used in the manufacturing of a specialty pigment.
3207 30 00		6794219/2023	1051	Silver containing paste which is used in printing process in the production of solar cells with: <ul style="list-style-type: none"> - a viscosity of 30 to 420 Pa.s at 10 rpm, - a solid percentage ranges between 59 % and 92 % and - a minimum 2 N/mm adhesion strength 	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/7 used in printing process in the production of solar cells.

3212 90 00		6483925/2023	1025	Aluminum paste, which is used in the production of solar cells, - with a viscosity of ranging from 10 to 100 Pa.s at 20 rpm, - with a solid percentage ranging from 72 % to 82 %, finess of grind less than 26 microns	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/7 used in the production of solar cells.
3214 10 10		6794307/2023	1050	Silicon frame: - in the colors of black and white, - with the density of $1,39 \pm 0,05 \text{ g/cm}^3$, - with a tensile strength of 2,0 mPA or more, - with an adhesive time 5-20 minutes used in the manufacture of solar panels with the purpose of sticking the junction box to the panel (2)	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/7 used in the production of solar cells.
3603 50 00		6650897/2023	1046	Igniters for gas generators with: - an overall length of 15,5 mm or more but not more than 22,5 mm, - a width of 7,8 mm or more but not more than 21 mm, - a pin length of 6,4 mm or more but not more than 12,6 mm, - a weight of not more than 29 g, - a small amount of explosive substances	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 Intended use: Automotive airbag inflator component.
3811 29 00		6609772/2023	1953	Additive for lubricating oils consisting of the reaction product of <i>bis</i> (dibutylcarbomodithioato)di- μ -oxodioxodi-molydiene with sulfur (CAS RN 68412-26-0)	S	New	UNDER EXAMINATION	DE	Applicant	Round 2024/07 used in the production of lubricants.
3824 99 92		6597948/2023	1038B	Mixture containing by weight of: - 50 % (+- 1 %) ethylene carbonate (CAS RN 96-49-1) with a purity of 99,9 % or more and	S	New	UNDER EXAMINATION	HU	Applicant	Round 2024/7 - Raw material to be mixed with other raw materials, used in a closed technological

3914 90 00		6795981/2023	1047	Silicone potting material, - with A and B components, - mixed in certain proportions, - the viscosity of the mixture is in the range of 3 000-6 000 cps, used in solar panel manufacture as an electrical insulations material in the junction box (2)	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/7 used in the production of solar cells.
3919 90 80		6481327/2023	1024	Black poly (vinyl chloride) film: - with a gloss of more than 25 degrees according to ASTM D 2457, - whether or not covered on one side with a protective poly(ethyleneterephthalate) film, and on the other side with a pressure sensitive adhesive with channels and a release liner	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/7 used for production of vehicles.
3919 90 80		6660963/2023	1959	Polytetrafluoroethylene film, - with a thickness of 50 µm or more but not more than 165 µm, - with a width of 6,30 mm or more but not more than 740 mm, - an elongation at break of not more than 200 %, and - coated on one side with a pressure sensitive silicone adhesive with a thickness of not more than 50 µm	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 Polytetrafluoroethylene film
3926 90 97		6652706/2023	1956	Gaskets made of polyethylene foam, produced in the thermoforming process at a temperature of 140 °C or more, but not more than 160 °C, with: - density of 20 kg/m ³ or more, but not more than 40 kg/m ³ , - tensile strength of not less than 170 KPa, - water absorption coefficient of not greater than 1 %	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/07 for manufacture of car mirrors

4016 99 52		6598076/2023	1040	Hanger of the exhaust muffler consisting of: - a steel bracket with at least one mounting hole and - silent block for use in the manufacture of goods of Chapter 87 (2)	S	New	UNDER EXAMINATION	SK	Applicant	Round 2024/7 for use in the manufacture of goods of Chapter 87.
7009 91 00		6652503/2023	1955	(Automotive) Glass chromate mirror of: - a length of 155 mm or more, but not more than 158 mm, - a height of 115 mm or more, but not more than 120 mm, equipped with: - a blind spot sensor with a blind spot motion detection light module, with an edge luminescence greater than or equal to 5000 cd/m ² and a central luminescence greater than or equal to 7000 cd/m ² , - heater foil, with a resistance of 1,1 kOhm or more, but not more than 1,35 kOhm designed to be mounted in a housing as an exterior vehicle mirror	S	New	UNDER EXAMINATION	PL	Applicant	Round 24/07 for manufacture of car mirrors
7009 91 00		6651025/2023	1054	Unframed chromate glass for the manufacture of automotive mirrors: - of a length of 140 mm or more but not more than 215 mm, - of a height of 104 mm or more but not more than 138 mm, - of a radius of curvature of 0 mm or more but not more than greater than 1 330 mm, - with reflectance greater than 40 %, - aspherical, convex or flat, - ready for framing	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 used for manufacture of car mirrors.

7019 90 00		6262789/2023	1011	Vacuum insulation panels made of fiberglass for the manufacture of refrigerators and freezers and their combinations	S	New	UNDER EXAMINATION	DE	Applicant	Round 2024/7 used for the manufacture of refrigerators.
8202 99 80		6660034/2023	1958	Steel wire covered with diamond grains of 5-55 µm used for cropping and squaring semiconductors with a wire diameter of 45-350 µm, and a breaking strength between 11 and 170 N.	S	New	UNDER EXAMINATION	TR	Applicant	Round 2024/07 steel wire for solar module
8402 90 00		6663051/2023	1960P	Pre-assembled process module unit of an ethane cracker unit, containing: <ul style="list-style-type: none">- a dilution steam generator system which produces steam from pretreated quench water for use as dilution steam in steam cracking furnaces,- a condensate system that collects, filters and deaerates steam condensates, which are subsequently recycled as boiler feed water and further distributed within the cracker unit, and- a flare system that collects, separates and vaporizes non-recyclable hydrocarbon containing releases from different equipment in a steam cracker, and transfers those towards flares	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 Module for ethane cracker unit
8409 91 00		6509204/2023	1951	Carburetor of grass trimmer: <ul style="list-style-type: none">- to produce a fuel-air mix that powers a two-stroke engine,- with 2 mounting holes diameter of 31 mm,- with a choke bore diameter of 18 mm or more, but not more than 19,05 mm	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/07 used for the production of grass cutters and grass trimmers.
8414 59 25		6609413/2023	1045	Axial fans with built-in motor, for the generation of an air flow for the cooling	S	New	UNDER EXAMINATION	DE	Applicant	Round 2024/7 used in the manufacture of heat pump tumble dryers

				<p>of compressors and the distribution of air with</p> <ul style="list-style-type: none"> - voltage, when operating with direct current, higher than 10 V but not higher than 14 V, or - voltage, when operating with alternating current, higher than 185 V, but not higher than 254 V, - and operation at an operating temperature of -40° or higher, but not higher than 70° C, <p>for use in the manufacture of heat pump tumble dryers and refrigerators or freezers (2)</p>						and refrigerators or freezers.
8414 59 35		6598289/2023	1042B	<p>Electric blower for cooling the battery module with an operating voltage of 9 VDC or more but not more than 16 VDC, comprising:</p> <ul style="list-style-type: none"> - electric (centrifugal) fan, - connector, - plastic case, - whether or not control unit of fan electric motor, <p>for use in the production of rechargeable batteries for hybrid and electric vehicles (2)</p>	S	New	UNDER EXAMINATION	SK	Applicant	Round 2024/7 - intended for the production of an integrated battery system.
8417 80 50		6686031/2023	1964P	<p>Pre-assembled process module unit of an ethane cracker unit, containing two steam-cracking furnaces consisting of a radiation section and a convection section to produce ethylene and propylene from ethane</p>	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 module for ethane cracker unit
8419 40 00		6663370/2023	1961P	<p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> - quench water circulation loops, which contain a heat exchanger and circulation pumps to cool and recirculate quench water, 	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 module for ethane cracker unit

				<ul style="list-style-type: none"> - a water purification system, which removes hydrocarbon contaminants from quench water which is then re-used for dilution steam production (outside the module), - a pyrolysis oil purification system, which separates pyrolysis gasoline, heavy oil and coke fractions from the hydrocarbon contaminants that have been removed from the quench water, - an ethane feedstock start-up vaporizer and superheater, which vaporizes and heats ethane feedstock before sending the ethane to the cracking furnaces (outside the module), - a propane feedstock preparation system, which filters, vaporizes and superheats propane feedstock, before sending the propane to cracking furnaces (outside the module), and - a chemical grade propylene preparation system, which filters and dries chemical grade propylene before sending it to the deethanizer (outside the module) 						
8419 50 80		6686117/2023	1965P	<p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> - an open loop ethylene refrigeration system, which is to be integrated with an external ethylene refrigerant compressor, - pumps and a heat exchanger to deliver ethylene to an external pipeline, and - a closed loop propylene refrigeration system, which is to be integrated with an external propylene refrigerant compressor 	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 module for ethane cracker unit
8419 89 98		6685918/2023	1963P	<p>Pre-assembled process module unit of an ethane cracker unit, containing:</p>	S	New	UNDER EXAMINATION	BE	Co-applicant	Round 2024/07 module for ethane cracker unit

				<p>equipment associated with an external multi-stage, centrifugal cracked gas compressor which compresses hydrocarbon gases to allow further processing downstream in interconnected equipment containing:</p> <ul style="list-style-type: none"> - coolers, - vapor-liquid separation drums, and - pumps needed to condense and remove water and heavier hydrocarbons and to avoid undesirable formation of polymer by-products, <p>equipment associated with an external caustic wash tower containing:</p> <ul style="list-style-type: none"> - caustic water circulation pumps to support an external caustic wash tower in removing acid gasses (carbon dioxide and hydrogen sulphide) from the cracked gas, - a spent caustic pre-treatment system, containing separation drums, pumps and mixers, - a heat exchanger for the pre-cooling of cracked gas, and - a separation drum for the removal of water from cracker gas 						
8467 99 00		6509387/2023	1027	<p>Pole hedge trimmer cutting elements:</p> <ul style="list-style-type: none"> - in the form of hedge trimmer attachment, - with a knife length of 60 cm and teeth opening of 30 mm, - with angle adjustment of the blade, - with integrated single stage gearbox, - with a magnesium cast body 	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 used for the production of hedge trimmers.
8479 89 97		6685758/2023	1962P	<p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> - various distillation columns (depropanizer, debutanizer and degreenoiler) and their associated heat exchangers, pumps and drums, 	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 module for ethane cracker unit

				<ul style="list-style-type: none"> - a chilling train containing heat exchangers and a drum which condenses C2 in a gas stream, - a system to separate hydrogen and methane from cracked gas containing heat exchangers, drums, turbines, compressors and a hydrogen purification unit (pressure swing adsorption unit), - associated equipment of a C3 splitter distillation column, containing heat exchanger, pumps and drums, and - a vinyl acetylene hydrogenation system, containing hydrogenation reactors, filters, mixer, drum, condenser, heat exchangers 						
8479 89 97		6686336/2023	1966P	<p>Pre-assembled process module unit of an ethane cracker unit, containing:</p> <ul style="list-style-type: none"> - a system for filtering and cooling of dried cracked gas, - a deethanizer distillation column and associated equipment for C2-/C3+ separation, - an acetylene hydrogenation system to remove acetylene within a C2 stream, - a fuel gas drum that stores fuel gas for cracker furnaces, and - a system to regenerate dryers in a cracker installation 	S	New	UNDER EXAMINATION	BE	Applicant	Round 2024/07 module for ethane cracker unit
8483 40 23		6471403/2023	1021	<p>Bevel gear:</p> <ul style="list-style-type: none"> - made of lightweight alloys and steel, - built on straight or helical bevel gears, - with an angle of 30 degrees or more but not more than 90 degrees, - with 1:1.3 ratio or more but not more than 1:1.46 	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 used for the production of grass cutters and grass trimmers.

8483 40 23		6471276/2023	1020	Bevel gear: - made of lightweight alloys and steel, - built on straight bevel gears, - with an angle of 24 degrees or more but not more than 35 degrees	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 used for the production of grass cutters and grass trimmers.
8501 10 99		6652860/2023	1957	Direct current actuator with three electrical connectors, with: - 2 brushless motors, - output power not exceeding 37,5 W, - voltage of 10 V or more, but not more than 15 V, - operating temperature range at least -40 °C or less to 80 °C or more, - minimum vertical and horizontal tilt angles of 20 degrees from the main axis	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/07 for manufacture of car mirrors
8501 31 00		6509270/2023	1950	Brushless DC electric motors: - with a rated power of more than 240 W, but not more than 260 W, - with a voltage of 36 V or higher, but not higher than 52 V - with a torque of 35 Nm or more, but not more than 120 Nm, - with a housing made of aluminum or plastic, - with a built-in controller, - with a communication function in the UART or CAN interface, - weighing 2,25 kg or more, but not more than 3,4 kg, - adapted for mounting in a bicycle frame	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/07 parts for bicycles
8501 31 00		6509321/2023	1800	Brushless DC electric motors:	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7: For use in the manufacture of e-bikes

				<ul style="list-style-type: none"> - with a rated power of 240 W or more, but not more than 260 W, - with voltage of 36 V or higher, but not higher than 52 V, - with torque of 30 Nm or more, but not more than 50 Nm, - with communication function UART or CAN interface, - with internal planetary gearbox with fixed or variable ratio, - made by CNC machined casting, - with housing made of aluminum, - weighing 2.3 kg or more, but not more than 4.4 kg, - adapted for mounting in the front or rear bicycle wheel 						
8503 00 99		6647017/2023	2005	<p>Die cast aluminum inner housing of cooling channel system in an electrical motor:</p> <ul style="list-style-type: none"> - pressure-casted of EN AC-47100 aluminum, - shot-blasted, machined and mechanically cleaned, - leakproof to the degree of 3 ml per minute or less in 2,75 bar pressure, - of hardness of 70HBV 2,5/62.5 or more in the Brinell scale, - of tensile strength of 240N/mm² or higher,- with a height of 225mm or more, but not more than 280mm - with a diameter of 300mm or more, but not more than 310mm - with a weight of 3,8 kg or more, but not more than 4,9 kg 	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024.7- for use in the manufacture of electrical motors
8503 00 99		85030099	2006	<p>Die cast aluminum outer housing of an electrical motor:</p> <p>pressure-casted of EN AC-47100 aluminum,</p> <ul style="list-style-type: none"> - with overmolded bearing sleeves made of martensitic stainless steel and 	S	New	UNDER EXAMINATION	PL	Applicant	Round 20024.7 - for manufacturing electrical motors

				<p>assembled sealing caps of stainless steel,</p> <ul style="list-style-type: none"> - shot-blasted, machined and mechanically cleaned, - rotor chamber leakproof to the degree of 3 ml per minute or less in 2,75 bar pressure, - of hardness of 70 HBV 2,5/62.5 or more in the Brinell scale, - of tensile strength of 240 N/mm² or higher, - with a height of 245 mm or more, but not more than 360 mm - with a width of 360 mm or more, but not more than 525 mm - with a length of 345 mm or more, but not more than 450 mm - with a weight of 6,4 kg or more, but not more than 8,3 kg 						
8503 00 99		6650648/2023	2007	<p>Die cast aluminum rotor cover of cooling channel system in the electrical motor: pressure-casted of EN AC-47100-F aluminum,</p> <ul style="list-style-type: none"> - with a sealing cap of stainless steel, - shot-blasted, machined and mechanically cleaned, - leakproof to the degree of 1 ml per minute or less in 2,75 bar pressure, - of hardness of 70 HBV 2,5/62.5 or more in the Brinell scale, - of tensile strength of 240 N/mm² or higher, - with a height of 50 mm or more, but not more than 55 mm - with a diameter of 109 mm or more, but not more than 112 mm - with a weight of 3,9 kg or more but not more than 4,2 kg 	S	New	UNDER EXAMINATION	PL	Applicant	Round 20024.7 - used for the manufacture of electrical motors
8505 20 00		6471531/2023	1022	<p>Electric clutch:</p> <ul style="list-style-type: none"> - used in Rider type self-propelled mowers, 	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 is used for the production of ride-on front mowers.

				<ul style="list-style-type: none"> - transmitting torque from motor shaft to pulley for cutting device, - parameters: 12 V; 3,93 A current or more but not more than 6,86 A, 1,84 Ω resistance or more but not more than 3,05 Ω (operating at 20°C), - static torque of 108 Nm or more but not more than 305 Nm 						
8507 60 00		6609698/2023	1952B	<p>Modules for the assembly of batteries of ion lithium electric accumulators - in lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> - a length of 820 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh 	S	New	UNDER EXAMINATION	DE	Applicant	Round 2024/07 used for assembly of ion lithium electric accumulators, which will be incorporated in battery electric vehicles .
8507 60 00		6598010/2023	1039B	<p>Lithium-ion rechargeable battery cell with:</p> <ul style="list-style-type: none"> - a length of 190 mm or more but not more than 380 mm, - a width of 90 mm or more but not more than 150 mm, - a height of 4 mm or more but not more than 15 mm, - a weight 0,1 kg or more but not more than 1,2 kg, - a nominal voltage of 3,0 V or more but not more than 4,0 V, - a nominal capacity not more than of 90 Ah, <p>for use in the manufacture of rechargeable hybrid and electric vehicle batteries (2)</p>	S	New	UNDER EXAMINATION	SK	Applicant	Round 2024/7 intended for the production of car batteries .

8507 60 00		6609601/2023	2003B	Lithium-ion accumulator, with <ul style="list-style-type: none">- multiple connected lithium-ion accumulator cells,- charging and monitoring electronics,- a power of 74 Wh or more, but not more than 75 Wh,- in a plastic housing with electrical connection contacts and LC display, for use in the manufacture of cordless vacuum cleaners or for use as a rechargeable power source therefor (2)	S	New	UNDER EXAMINATION	DE	Applicant	Round 2024.7 - Battery related product
8511 80 00		6471603/2023	1023	Ignition module: <ul style="list-style-type: none">- used in two-stroke engines,- made of plastics and non-ferrous metals,- electric part protected by epoxy resin	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 used for the production of grass cutters and grass trimmers.
8512 20 00		6509491/2023	1028	An electrical component with an integrated LED, in an ABS housing, with: <ul style="list-style-type: none">- a voltage of 11 V or more, but not more than 15 V,- a circular shape,- 2 terminals,- an outer diameter of the housing of 36 mm or more, but not more than 39 mm,- diode voltage of 42 V or more, but not more than 48 V and amperage of 55 mA or more, but not more than 65 mA	S	New	UNDER EXAMINATION	PL	Applicant	Round 2024/7 For manufacture of car mirrors.
8537 10 98		6609501/2023	2002	Display and control unit for a household kitchen machine consisting of <ul style="list-style-type: none">- an electronic circuit with an LC color display with touch-sensitive surface and backlight,- four LEDs,	S	New	UNDER EXAMINATION	DE	Applicant	Round 2024.7 - Display and control unit. Part of an electric household kitchen machine

				- two flat ribbon cables with multiple plugs on the rear side, in a plastic housing with snap-in brackets on the rear side and a surrounding seal made of soft plastic						
8544 30 00		6598158/2023	1041B	Wiring harness for connecting the battery system with the car's control systems, containing: <ul style="list-style-type: none"> - an input waterproof connector, - four or more output connectors, - two or more plastic clips for attachment for use in the production of rechargeable batteries for hybrid and electric vehicles (2)	S	New	UNDER EXAMINATION	SK	Applicant	Round 2024/7 used in the production of rechargeable batteries for hybrid and electric vehicles.
ex 1517 90 99	10	833/06 PROLONG 2022	0503	IE(15.09.2023) new text proposal: Vegetable and/or microbial fats oil, refined, containing by weight 25 % or more but not more than 50 % Arachidonic acid or 12 % or more but not more than 65 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO) HU(13.09.2023) new text proposal: Vegetable oil, refined, containing by weight 25 % or more but not more than 70 % arachidonic acid or 12 % or more but not more than 65 % docosahexaenoic acid and standardized or not with high oleic sunflower oil (HOSO), whether or not containing by weight 0,005 % or more, but not more than 0,05 % rosemary olerosin and 0,005 % or more, but not more than 0,05 % rapeseed vegetable oil --- Current description:	S	Amendment	UNDER EXAMINATION	NL	Applicant	Round 2024-07- request for amendment.

				Vegetable oil, refined, containing by weight 25 % or more but not more than 50 % arachidonic acid or 12 % or more but not more than 65 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO)						
ex 2008 93 91	20	247869/2009 PROLONG 2023	0580	Sweetened dried cranberries, excluding packing alone as processing, for the manufacture of products of food processing industries (1)	S	Amendment	UNDER EXAMINATION	DE CZ ES PL	Applicant Co-applicant Co-applicant Co-applicant	Round 2024-07 - request for amendment. Poland would like to discuss and hear an opinion of the Commission and MS on footnote TN085 concerning pasteurisation process for sweetened dried cranberries.
ex 2818 10 91	20	589575/2010 PROLONG 2021	0518	AT(11.09.2023) request for amendment: Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight (calculated as oxides) of: - 92 % or more, but less than 98,5 % of aluminium oxide, - 2 % (\pm 1,5 %) of magnesium oxide, - 1 % (\pm 0,6 %) of yttrium oxide, and - either 3 % (\pm 2,2 %) of lanthanum oxide or - 2 % (\pm 1,2 %) of lanthanum oxide and neodymium oxide, with less than 50 % of the total weight having a particle size of more than 10 mm	S	Amendment	UNDER EXAMINATION	AT	Applicant	ROUND 2024/07: request for amendment. // used for the production of vitrified and resinoid bonded grinding wheels.

				<p>---</p> <p>Current text: Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight (calculated as oxides) of:</p> <ul style="list-style-type: none"> - 94 % or more, but less than 98,5 % of aluminium oxide, - 2 % (\pm 1,5 %) of magnesium oxide, - 1 % (\pm 0,6 %) of yttrium oxide, <p>and</p> <ul style="list-style-type: none"> - either 2 % (\pm 1,2 %) of lanthanum oxide, or - 2 % (\pm 1,2 %) of lanthanum oxide and neodymium oxide, <p>with less than 50 % of the total weight having a particle size of more than 10 mm</p>						
ex 2933 79 00	80	1818416/2022	0519	<p>ES(08.09.2023) request for amendment: (S)-2-Amino-3-[(S)-2-oxopyrrolidin-3-yl]propanamide hydrochloride (CAS RN 2628280-48-6) with a purity by weight of 90 % or more</p> <p>---</p> <p>Current text: (S)-2-Amino-3-[(S)-2-oxopyrrolidin-3-yl]propanamide hydrochloride (CAS RN 2628280-48-6) with a purity by weight of 98 % or more</p>	S	Amendment	UNDER EXAMINATION	ES	Applicant	Round 2024-07 - request for amendment. // for use in the manufacturing of a new Active Pharmaceutical Ingredient
ex 2933 99 80	17	1848678/2022	0520	<p>ES(08.09.2023) request for amendment:</p>	S	Amendment	UNDER EXAMINATION	ES	Applicant	Round 2024-07: request for amendment. //

				(1R,2S,5S)-3-[(S)-3,3-dimethyl-2-(2,2,2-trifluoroacetamido)butanoyl]-6,6-dimethyl-3-azabicyclo[3.1.0]hexane-2-carboxylic acid (CAS RN 2755812-45-2) with a purity by weight of 90 % or more --- Current description: (1R,2S,5S)-3-[(S)-3,3-dimethyl-2-(2,2,2-trifluoroacetamido)butanoyl]-6,6-dimethyl-3-azabicyclo[3.1.0]hexane-2-carboxylic acid (CAS RN 2755812-45-2) with a purity by weight of 98 % or more						Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity).
ex 2939 79 90	50	1765066/2021	0590	1-Alpha-H,5-alpha-H-Nortropan-3-alpha-ol (CAS RN 538-09-0) with a purity by weight of 99 % or more	S	Amendment	UNDER EXAMINATION	IT	Applicant	Round 20214-07 - To be deleted -duty free. Used as raw material in the chemical synthesis for the production of active pharmaceutical ingredients.
ex 2939 79 90	60	1225963/2018 PROLONG 2024	0591	4-Methyl-2-pyridylamine (CAS RN 695-34-1) with a purity by weight of 98 % or more	S	Amendment	UNDER EXAMINATION	IT	Applicant	Round 2024-07 - to be deleted - duty free. intermediate for the production of the raw material used for Antibacterial Antibiotics
ex 3801 10 00	20	1816782/2020	0500B	Artificial graphite (CAS RN 7782-42-5) powder form, with: - specific surface area (measured by BET) of 0,8 m ² /g (± 0,25), - tap density: 0,85 g/cm ³ (± 0,10), - particle size represented by d50 value of 21,0 µm (± 2,0), - specific discharge capacity of 351,0 mAh/g (± 3,0),	S	Amendment	UNDER EXAMINATION	PL EU FR	Applicant Opposed Opposed	Round 2024 - 07 - Objection. Artificial Graphite powder form for production of batteries.

				- initial efficiency of 94,0 % ($\pm 2,0$)						
ex 3801 10 00	30	1731611/2020	0501B	Artificial graphite in powder form, (CAS RN 7782-42-5) with: <ul style="list-style-type: none"> - with or without coating on the surface, - particle size represented by d50 value of 15 μm (± 4), - specific surface area (measured by BET) less than 3,5 m^2/g, - tap density: 1,3 g/m^3 ($\pm 0,5$), - specific Discharge Capacity of 348 mAh/g (± 13), - initial efficiency above 93,0 % 	S	Amendment	UNDER EXAMINATION	SE DE DE EU EU FR FR	Applicant Co-applicant Opposed Opposed Opposed Opposed Opposed	Round 2024-07 - review of the suspension and objection.// Artificial graphite for production of batteries.
ex 3811 21 00	48	827339/2014 PROLONG 2020 Prologation exercise 1/1/2019	0509	FR(13.09.2023) new proposal: Additives containing: <ul style="list-style-type: none"> - overbased magnesium (C20-C24) alkylbenzenesulphonates (CAS RN 231297-75-9) and - by weight more than 25 % but not more than 50 % of mineral oils, - having a total base number of more than 350, but not more than 450, for use in the manufacture of lubricating oils or for use in the manufacture of blends of additives for lubricating oils (2) <p>---</p> Current text: Additives containing <ul style="list-style-type: none"> - overbased magnesium (C20-C24) alkylbenzenesulphonates (CAS RN 231297-75-9) and - by weight more than 25 % but not more than 50 % of mineral oils, having a total base number of more than 350, but not more than 450, for use in the manufacture of lubricating oils	S	Amendment	UNDER EXAMINATION	FR	Applicant	Round 2024-07 - request for amendment + new co-applicant.// In the EU the imported product is blended to make complex blends, combining multiple components, to form sophisticated and performance enhancing lubricant additive concentrates for gear oils

				(2)						
ex 3811 21 00	50	335288/2012 PROLONG 2023	0508	<p>FR(14.09.2023) new proposal: Additive containing:</p> <ul style="list-style-type: none"> - calcium C16-24 alkylbenzenesulphonates (CAS RN 70024-69-0), - 30 % or more but not more than 65 % by weight of mineral oils, <p>used in the manufacture of blends of additives for lubricating oils</p> <p>---</p> <p>Current text: Additives for lubricating oils,</p> <ul style="list-style-type: none"> - based on calcium C16-24 alkylbenzenesulphonates (CAS RN 70024-69-0), - containing mineral oils, <p>used as a concentrated additive for the manufacture of engine oils through a blending process</p>	S	Amendment	UNDER EXAMINATION	FR FR	Applicant Co-applicant	<p>Round 2024-07 - request for amendment and adding a co-applicant.//</p> <p>Detergent used in lubricants to keep engines clean and free of corrosive acids</p>
3812 39 90 ex 3824 99 93	72	1957248/2022	0513	<p>DE(13.09.2023) new proposal: Light stabilizer, reaction product of stearic acid methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) with a purity of less than 90 % by weight</p> <p>---</p> <p>Current text: Reaction product of octadecanoic acid methyl ester, with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6)</p>	S	Amendment	UNDER EXAMINATION	DE	Applicant	<p>Round 2024-07: request for amendment.</p> <p>Production of plastics that are particularly weather-resistant outdoors</p>

ex 3920 62 19	32	1304/2008 238080/2009 PROLONG 2019	0506	Transparent poly(ethylene terephthalate) film: - having thickness of both sides of 7 nm or more but not more than 80 nm, or thickness of both sides of 7 µm or more but not more than 80 µm, whether coated with an acrylic-based organic material or not, - with a surface tension of 36 Dyne/cm or more but not more than 39 Dyne/cm, or transparent 3 or 4 layers, second layer of PET, and other layers contain fluorine resin, - with a light transmittance of more than 80 %, - with a haze value of not more than 1,3 %, - with a total thickness of 10 µm or more but not more than 350 µm, - with a width of 800 mm or more but not more than 1 600 mm	S	Amendment	UNDER EXAMINATION	PL	Applicant	Round 2024-07 roll over request for amendment//
ex 3921 90 55	60	5869940/2021	0514	HU(13.09.2023) new proposal: Membrane composed of a polyamide layer and a polysulfone layer on a polyethylene terephthalate support layer with: - a total thickness of 0,25 mm or more but not more than 0,40 mm, - a total weight of 109 g/m ² or more but not more than 114 g/m ² --- Current text: Membrane composed of a polyamide layer and a polysulfone layer on a cellulose support layer with: - a total thickness of 0,25 mm or more but not more than 0,40 mm,	S	Amendment	UNDER EXAMINATION	HU	Applicant	Round 2024-07: request for amendment. The imported product consists of three layers: two layers of polyamide and polysulfone are built on the cellulose membrane support layer. This set up makes the membranes capable to be used in different industrial areas, like wastewater treatment, brine purification & organic fractionation.

				- a total weight of 109 g/m ² or more but not more than 114 g/m ²						
ex 4411 12 92	10	1987309/2022	0502	<p>SL(05.09.2023) proposal to remove the end-use: Fibreboard:</p> <ul style="list-style-type: none"> - with a thickness of 2,20 mm or more but not more than 2,80 mm, - with a density of 0,95 g/cm³ or more, - lacquered or coated with melamine foil on both sides, and - with dimensions of 1 300 mm x 1 100 mm or less <p>---</p> <p>current text: Fibreboard:</p> <ul style="list-style-type: none"> - with a thickness of 2,20 mm or more but not more than 2,80 mm, - with a density of 0,95 g/cm³ or more, - lacquered or coated with melamine foil on both sides, and - with dimensions of 1 300 mm x 1 100 mm or less, <p>used in the manufacture of printed circuit boards (2)</p>	S	Amendment	UNDER EXAMINATION	SI	Applicant	<p>Round 2024-07 request for removing the end use.//</p> <p>made for the production of printed circuit boards are used only for drilling, for the process by which printed circuit boards are made.</p>
ex 8479 89 97	28	4944174/2020	0504	<p>SK(11.09.2023) new text proposal: Integrated electric brake unit for immediate generation of the hydraulic pressure during braking, full electronic brake control and enabling regenerative braking of motor vehicles with:</p> <ul style="list-style-type: none"> - electronic brake assistants, - hydraulic unit driven by brushless electric motor, - brake fluid reservoir, 	S	Amendment	UNDER EXAMINATION	SK	Applicant	<p>Round 2024-07 Request for amendment.</p> <p>Integrated electric brake unit</p>

				<p>for use in the manufacture of hybrid passenger cars (2)</p> <p>---</p> <p>Current text: Integrated electric brake unit for immediate generation of the hydraulic pressure during braking, full electronic brake control and enabling regenerative braking of motor vehicles with:</p> <ul style="list-style-type: none"> - electronic brake assistants, - hydraulic unit driven by brushless electric motor, - brake fluid reservoir, <p>for use in the manufacture of plug-in hybrid passenger cars (2)</p>						
ex 8501 31 00	50	313124/2012 PROLONG 2023	0511	<p>PL(12.09.2023) new proposal: DC motors, brushless, with:</p> <ul style="list-style-type: none"> - an external diameter of 80 mm or more, but not more than 200 mm, - a supply voltage of 4V or more, but not more than 16 V, - an output at 20 °C of 200 W or more, but not more than 750 W, - a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm, - a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm, - with or without a pulley, - with or without an electronic power steering sensor/controller <p>---</p> <p>current text: DC motors, brushless, with:</p>	S	Amendment	UNDER EXAMINATION	PL	Applicant	<p>Round 2024-07 - request for amendment.//</p> <p>Electric motors in question are used for production of electric power steering systems suitable for cars</p>

				<ul style="list-style-type: none"> - an external diameter of 80 mm or more, but not more than 200 mm, - a supply voltage of 9 V or more, but not more than 16 V, - an output at 20 °C of 300 W or more, but not more than 750 W, - a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm, - a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm, - with or without a pulley, - with or without an electronic power steering sensor/controller 						
ex 8501 31 00 ex 8501 32 00	55 40	371604/2013 PROLONG 2019 PROLONG 2024	0516	<p>DE(12.09.2023) new proposal: DC motor with or without commutator, with</p> <ul style="list-style-type: none"> - an external diameter of 24,2 mm or more, but not more than 140 mm, - a rated speed of 3 300 rpm or more, but not more than 26 200 rpm, - a rated supply voltage of 3,6 V or more, but not more than 230 V, - an output power of more than 37,5 W, but not more than 2 400 W, - a free load current of not more than 20,1 A, - a maximum efficiency of 50 % or more, <p>for driving hand-held power tools, lawn mowers or home appliances</p> <p>---</p> <p>Current text: DC motor with or without commutator, with</p> <ul style="list-style-type: none"> - an external diameter of 24,2 mm or more, but not more than 140 mm, - a rated speed of 3 300 rpm or more, but not more than 26 200 rpm, 	S	Amendment	UNDER EXAMINATION	HU	Applicant	<p>Round 2024-07:request for amendment.//</p> <p>DC motors are built in in hand-held power tools (for example: screwdrivers), and drive assembled machines. DC motor can operate from battery as well as from mains power</p>

				<ul style="list-style-type: none"> - a rated supply voltage of 3,6 V or more, but not more than 230 V, - an output power of more than 37,5 W, but not more than 2400 W, - a free load current of not more than 20,1 A, - a maximum efficiency of 50 % or more, <p>for driving hand-held power tools or lawn mowers</p>						
ex 8501 31 00	58	229971/2009 PROLONG 2015 PROLONG 2020	0515	<p>HU(12.09.2023) requested change in 1st and 2nd intent:</p> <p>Permanently excited DC motor with:</p> <ul style="list-style-type: none"> - an external diameter of 27 mm or more but not more than 90 mm, including mounting flange, - a rated speed of not more than 25 000 rpm, - an output of 45 W or more but not more than 400 W, and - a supply voltage of 9 V or more but not more than 50 V, - whether or not a multiple-phase winding, - whether or not with a drive disc, - whether or not with a crankcase, - whether or not with a fan, - whether or not with a cap assembly, - whether or not with a sun gear, - whether or not with a speed and rotational direction encoder, - whether or not with or without a speed or rotational direction sensor of resolver type or Hall effect type, - whether or not with a mounting flange <p>for use in the manufacture of air suspension seats in tractors, earthmoving machines and forklifts or for use in the manufacture of actuators for height-adjustable furniture (2)</p>	S	Amendment	UNDER EXAMINATION	AT	Applicant	Round 2024-07: Request for amendment.

				<p>---</p> <p>Current text: Permanently excited DC motor with:</p> <ul style="list-style-type: none"> - an external diameter of 30 mm or more but not more than 90 mm, including mounting flange, - a rated speed of not more than 15 000 rpm, - an output of 45 W or more but not more than 400 W, and - a supply voltage of 9 V or more but not more than 50 V, - whether or not a multiple-phase winding, - whether or not with a drive disc, - whether or not with a crankcase, - whether or not with a fan, - whether or not with a cap assembly, - whether or not with a sun gear, - whether or not with a speed and rotational direction encoder, - whether or not with or without a speed or rotational direction sensor of resolver type or Hall effect type, - whether or not with a mounting flange <p>for use in the manufacture of air suspension seats in tractors, earthmoving machines and forklifts or for use in the manufacture of actuators for height-adjustable furniture (2)</p>							
ex 8505 11 10	47	1301940/2016 PROLONG 2022	0550M	<p>DE(12.09.2023) request for amendment: Articles in the form of a triangle, square, rectangle, or trapezoid, whether or not arched, with rounded corners or oblique</p>	S	Amendment	UNDER EXAMINATION	SK	Applicant	Round 2024-07 - request for amendment.// Round 2023-01: Combined	

				<p>sides, color market or not, with coated surface or not, whether or not consisting of several segments bonded together and electrically insulated from one another, intended to become permanent magnets after magnetisation, containing neodymium, iron and boron, with the following dimensions:</p> <ul style="list-style-type: none"> - a length of 9 mm or more but not more than 105 mm, - a width of 5 mm or more but not more than 105 mm, and - a height of 2 mm or more but not more than 55 mm <p>***</p> <p>DE(28.07.2023): Permanent magnets and articles intended to become permanent magnets after magnetisation, of an alloy of neodymium or an alloy of samarium, in the form of a triangle, a square, a rectangle, a trapezoid or bonded segments,</p> <ul style="list-style-type: none"> - whether or not arched, - whether or not with rounded corners or oblique sides - whether or not coated or [passivated] [with a surface treatment] <p>***</p> <p>NL(28.03.2023) : Articles, of an alloy of neodymium, in the form of a triangle, square, rectangle, or trapezoid, whether or not arched, with: rounded corners or oblique sides,</p> <ul style="list-style-type: none"> - a length of 9 mm or more but not more than 105 mm, - a width of 5 mm or more but not more than 105 mm, and - a thickness of 2 mm or more but not more than 55 mm 						<p>nomenclature change. 85051100 replaced with 85051110// Round 2022/7 Req for amendment Prolongation Exercise 2022-01-01 ROUND 07/2020: request for amendment.</p>
--	--	--	--	---	--	--	--	--	--	--

				<p>intended to become permanent magnets after magnetisation</p> <p>***</p> <p>or</p> <p>NL(28.03.2023) Proposal to merge suspension 85051110** (TARIC suffix 47, 50, 65, 68, 73, 75):</p> <p>Articles, of an alloy of neodymium or an alloy of samarium, in the form of a triangle, square, rectangle, or trapezoid, whether or not arched, whether or not with rounded corners or oblique sides whether or not coated or [passivated] [with a surface treatment] with a length of 9 mm or more but not more than 140 mm, a width of 5 mm or more but not more than 105 mm, and a thickness of 1,3 mm or more but not more than 55 mm</p> <p>---</p> <p>Current text:</p> <p>Articles in the form of a triangle, square, rectangle, or trapezoid, whether or not arched, with rounded corners or oblique sides, intended to become permanent magnets after magnetisation, containing neodymium, iron and boron, with the following dimensions:</p> <ul style="list-style-type: none">- a length of 9 mm or more but not more than 105 mm,- a width of 5 mm or more but not more than 105 mm, and- a height of 2 mm or more but not more than 55 mm						
--	--	--	--	--	--	--	--	--	--	--

ex 8505 11 10	50	312921/2012	0551M	<p>NL(28.03.2023) : Bars specifically shaped, of an alloy of neodymium, with:</p> <ul style="list-style-type: none">- a length of 15 mm or more but not more than 52 mm,- a width of 5 mm or more but not more than 42 mm, <p>intended to become permanent magnets after magnetisation, [of a kind to be used in the manufacture of electric servomotors for industrial automation]</p> <p>***</p> <p>or</p> <p>NL(28.03.2023) Proposal to merge suspension 85051110** (TARIC suffix 47, 50, 65, 68, 73, 75): Articles, of an alloy of neodymium or an alloy of samarium, in the form of a triangle, square, rectangle, or trapezoid,</p> <ul style="list-style-type: none">- whether or not arched,- whether or not with rounded corners or oblique sides- whether or not coated or [passivated] [with a surface treatment]- with- a length of 9 mm or more but not more than 140 mm,- a width of 5 mm or more but not more than 105 mm, and- a thickness of 1,3 mm or more but not more than 55 mm <p>---</p> <p>Current text: Bars specifically shaped, intended to become permanent magnets after magnetisation, containing neodymium, iron and boron, with dimensions:</p>	S	Amendment	UNDER EXAMINATION	PL	Applicant	<p>Round 2024-07 - request for amendment</p> <p>It is intended to be incorporated into electrical motors designed for industrial automation</p>
---------------	----	-------------	-------	---	---	------------------	-------------------	----	-----------	---

				<ul style="list-style-type: none"> - a length of 15 mm or more but not more than 52 mm, - a width of 5 mm or more but not more than 42 mm, of a kind to be used in the manufacture of electric servomotors for industrial automation						
ex 8505 11 10	53	1431341/2018 PROLONG 2024	0553M	<p>NL(28.03.2023): Permanent magnets, of an alloy of neodymium, cylindrical shaped, with:</p> <ul style="list-style-type: none"> - a notch - an internal threaded bore on one side, - a length of 97,5 mm or more, but not more than 225 mm - a diameter of 19 mm or more, but not more than 25 mm <p>** Or NL (28.03.2023) Merging suspensions under 85051110** (TARIC suffix 53,63,65,70): Articles, of an alloy of neodymium or an alloy of samarium, in the form of a cylinder, disc, ring, tube, bushing or collar,</p> <ul style="list-style-type: none"> - whether or not coated or [passivated] [with a surface treatment] - whether or not with a centre hole - whether or not with a notch and an internal threaded bore on one side with - an external diameter of not more than 90 mm - an height of not more than 225 mm <p>--- Current text:</p>	S	Amendment	UNDER EXAMINATION	UK	Applicant	<p>Round 2024-07 - new applicant needed + request for amendment ././</p> <p>Used in the manufacture of domestic and industrial central heating systems</p>

				Permanent magnets of a neodymium alloy cylindrical shaped with notch with internal threaded bore on one side, with <ul style="list-style-type: none"> - a length of 97,5 mm or more, but not more than 225 mm - a diameter of 19 mm or more, but not more than 25 mm 						
ex 8505 11 10	63	312685/2012	0554M	<p>NL(28.03.2023): Articles of an alloy of neodymium, in the form of rings, tubes, bushings or collars with:</p> <ul style="list-style-type: none"> - an external diameter of not more than 45 mm, - a height of not more than 45 mm, <p>intended to become permanent magnets after magnetisation</p> <p>---</p> <p>current text: Rings, tubes, bushings or collars made from an alloy of neodymium, iron and boron, with</p> <ul style="list-style-type: none"> - an external diameter of not more than 45 mm, - a height of not more than 45 mm, <p>of a kind used in the manufacture of permanent magnets after magnetisation</p>	S	Amendment	UNDER EXAMINATION	DE	Applicant	The NdFeB magnets are for use in an electric motor (synchronous motor). Depending on the application of magnetic systems it is used in a variety of automotive technology. It is used here in a steering motor (electric power steering).
ex 8505 11 10	65	2520/3/2004 873/2005 PROLONG 2019 PROLONG 2024	0555M	<p>NL(28.03.2024) request for amendment: Permanent magnets of an alloy of neodymium, either in the shape of a rectangle, whether or not rounded, with</p> <ul style="list-style-type: none"> - a rectangular or a trapezoidal [cross-]section - a length of not more than 140 mm, - a width of not more than 90 mm and - a thickness of not more than 55 mm, 	S	Amendment	UNDER EXAMINATION	NL BE DE	Applicant Co-applicant Co-applicant	Round 2024-07 – request for amendment

				<p>or in the shape of an arched rectangle with:</p> <ul style="list-style-type: none"> - a length of not more than 75 mm, - a width of not more than 40 mm, - a thickness of not more than 7 mm and - [a radius of curvature of more than 86 mm but not more than 241 mm] - layers of nickel and copper <p>or in the shape of a disc with:</p> <ul style="list-style-type: none"> - a diameter of not more than 90 mm, - whether or not a hole in the centre <p>---</p> <p>Current text: Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rectangle, whether or not rounded, with a rectangular or a trapezoidal section having</p> <ul style="list-style-type: none"> - a length of not more than 140 mm, - a width of not more than 90 mm and - a thickness of not more than 55 mm, <p>or in the shape of curved rectangle (tile type) having</p> <ul style="list-style-type: none"> - a length of not more than 75 mm, - a width of not more than 40 mm, - a thickness of not more than 7 mm and - a radius of curvature of more than 86 mm but not more than 241 mm <p>or in the shape of a disc with a diameter of not more than 90 mm, whether or not containing a hole in the centre</p>							
ex 8505 11 10	68	2200145/2019	0556M	<p>NL (28.03.2023) request for amendment: Articles of an alloy of neodymium, or an alloy of samarium, whether or not</p>	S	Amendment	UNDER EXAMINATION	SI	Applicant	Round 2024-07 - request for amendment. //	

				<p>covered with zinc, in the shape of rectangles with:</p> <ul style="list-style-type: none"> - a length of 13,8 mm or more but not more than 45,2 mm, - a width of 7,8 mm or more but not more than 25,2 mm, - a height of 1,3 mm or more but not more than 4,7 mm, <p>intended to become permanent magnets after magnetisation</p> <p>---</p> <p>Current text: Blocks made of neodymium, iron and boron or an alloy of samarium and cobalt, whether or not covered with zinc, intended to become permanent magnets after magnetisation with:</p> <ul style="list-style-type: none"> - a length of 13,8 mm or more but not more than 45,2 mm, - a width of 7,8 mm or more but not more than 25,2 mm, - a height of 1,3 mm or more but not more than 4,7 mm 						<p>Round 2023-01 - Prolongation item, 5 years + change in CN code- Old code 85051100 (68), New code 85051110 (68)// Round 2021-01 - request for amendment Round 2020-01 to be further on installed into electromotors</p>
ex 8505 11 10	70	343278/2013 PROLONG 2019 PROLONG 2024	0557M	<p>NL(28.03.2023) request for amendment: Article of an alloy of neodymium, in the shape of a disc , with</p> <ul style="list-style-type: none"> - a diameter of not more than 90 mm, - whether or not a hole in the centre, - layers of copper, nickel and/or zinc <p>intended to become permanent magnets after magnetisation, [of a kind used in car loudspeakers]</p> <p>---</p> <p>Current text:</p>	S	Amendment	UNDER EXAMINATION	PL	Applicant	<p>Prolongation Exercise 2024-01-01</p> <p>>>> Commercial denomination: Neodymium magnet >>> Application and use: Articles (discs) intended to become permanent magnets after magnetisation (commonly referred to in commerce as: neodymium magnets) are used for the production of car loudspeakers.</p>

				<p>Disc consisting of an alloy of neodymium, iron and boron, covered with nickel or zinc, that after magnetisation is intended to become a permanent magnet</p> <ul style="list-style-type: none"> - whether or not containing a hole in the centre, - with a diameter of not more than 90 mm, <p>of a kind used in car loudspeakers</p>						
<p>ex 8505 11 10 ex 8505 11 90 ex 8505 19 90</p>	<p>73 73 35</p>	3869544/2015	0552M	<p>FI(15.09.2023) request for amendment: Articles in shape of flat bars, arched bars, quarter sleeves or trapezoid whether or not arched, rounded corners or oblique sides made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, whether or not overmolded with polymers, intended to become permanent magnets after magnetisation with:</p> <ul style="list-style-type: none"> - a length of 5 mm or more, but not more than 60 mm, - a width of 5 mm or more, but not more than 40 mm, - a thickness of 3 mm or more, but not more than 15 mm <p>*** NL(28.03.2023): Articles in shape of flat bars, arched bars or quarter sleeves, made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, whether or not overmolded with polymers, intended to become permanent magnets after magnetisation with:</p> <ul style="list-style-type: none"> - a length of 5 mm or more, but not more than 60 mm, - a width of 5 mm or more, but not more than 40 mm, 	S	Amendment	UNDER EXAMINATION	PL	Applicant	<p>Round 2024-07- request for amendment.//</p> <p>Samarium-cobalt and ferrite magnets are an essential parts of car starters and devices extending the range of electric cars</p>

				<p>- a thickness of 3 mm or more, but not more than 15 mm</p> <p>***</p> <p>OR</p> <p>NL(28.03.2023) - Proposal to merge suspension 85051110** (TARIC suffix 73, 75) with 8505191020 and 85051990 (TARIC suffix 35,50,60):</p> <p>Articles, of agglomerated ferrite, in the form of a rectangle,</p> <ul style="list-style-type: none">- whether or not arched,- whether or not with rounded corners or oblique sides,- whether or not coated or [passivated] [with a surface treatment] <p>with:</p> <ul style="list-style-type: none">- a length of 5 mm or more, but not more than 111 mm,- a width of 5 mm or more, but not more than 101 mm,- a thickness of 1,85 mm or more, but not more than 15 mm <p>---</p> <p>Current text:</p> <p>Articles in shape of flat bars, arched bars or quarter sleeves, made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, whether or not overmolded with polymers, intended to become permanent magnets after magnetisation with:</p> <ul style="list-style-type: none">- a length of 5 mm or more, but not more than 60 mm,- a width of 5 mm or more, but not more than 40 mm,- a thickness of 3 mm or more, but not more than 15 mm						
--	--	--	--	---	--	--	--	--	--	--

ex 8505 11 10 ex 8505 11 90	75 75	816924/2014 PROLONG 2020	0558M	<p>NL(28.03.2023) request for amendment: Article of an alloy of neodymium, in the form of arched rectangles with</p> <ul style="list-style-type: none"> - a width of 9,1 mm or more but not more than 10,5 mm, - a length of 20 mm or more but not more than 30,1 mm, <p>[of a kind used on rotors for the manufacture of fuel pumps]intended to become permanent magnets after magnetization</p> <p>---</p> <p>Current text: A quarter sleeve intended to become permanent magnet after magnetization,</p> <ul style="list-style-type: none"> - consisting of at least neodymium, iron and boron, - with a width of 9,1 mm or more but not more than 10,5 mm, - with a length of 20 mm or more but not more than 30,1 mm, <p>of a kind used on rotors for the manufacture of fuel pumps</p>	S	Amendment	UNDER EXAMINATION	PL	Applicant	<p>Round 2024-07 - request for amendment.//</p> <p>Articles (neodymium magnets) which are subject of this application are used for production of rotors which, in turn, are an integral part of the fuel pump.</p>
ex 8505 11 10	78	6620328/2022	0563M	<p>Two permanent magnets made of a praseodymium-neodymium alloy, in a rectangular steel holder with an outer casing of rubber with outer dimensions:</p> <ul style="list-style-type: none"> - a length of 200 mm or more but not more than 205 mm, - a width of 58 mm or more but not more than 62 mm, - a height of 25 mm or more but not more than 30 mm, <p>with a stud mounted in the middle</p>	S	Amendment	UNDER EXAMINATION	DK	Applicant	<p>Round 2024-07 request for amendment. Possible merge with existing suspensions for permanent magnets.//</p> <p>Parts for renewable energy sector</p>
ex 8505 19 10	20	2200205/2019	0559M	<p>NL(28.03.2023) request for amendment:</p>	S	Amendment	UNDER EXAMINATION	SI	Applicant	Round 2024-07 request for amendment.//

				<p>Articles of agglomerated ferrite in the form of a disc,</p> <ul style="list-style-type: none"> - whether or not with a centre hole, - whether or not coated or [passivated] [with a surface treatment], - with an external diameter of not more than 120 mm, - with an height of not more than 15 mm <p>---</p> <p>Current text:</p> <p>Articles of agglomerated ferrite in the shape of a disc with a diameter of not more than 120 mm, containing a hole in the centre intended to become permanent magnets after magnetisation with a remanence between 245 mT and 470 mT</p>						
ex 8505 19 90	50	1514450/2017 PROLONG 2023	0561M	<p>NL(28.03.2023) request for amendment:</p> <p>Article of agglomerated ferrite in the shape of a rectangle, whether or not with oblique sides, with:</p> <ul style="list-style-type: none"> - a length of 26,85 mm or more but not more than 32,15 mm, - a width of 7,6 mm or more but not more than 9,55 mm, - a thickness of 5,3 mm or more but not more than 5,8 mm, and - a weight of 6,1 g or more but not more than 8,3 g, <p>intended to become a permanent magnet after magnetisation</p> <p>---</p> <p>Current text:</p>	S	Amendment	UNDER EXAMINATION	FR	Applicant	<p>Round 2024-07 request for amendment.// Prolongation Exercise 2023-01-01</p> <p>Round 2018-07: p/st was added as a suppl.unit</p> <p>ROUND 2018-01</p> <p>The role of the magnets assembled with the rotor is to generate a magnetic voltage at the terminals of the stator coil during the rotation of the rotor in the alternator.</p>

				<p>Article of agglomerated ferrite in the shape of a rectangular prism to become a permanent magnet after magnetisation</p> <ul style="list-style-type: none"> - whether or not with bevelled edges - of a length of 27 mm or more but not more than 32 mm ($\pm 0,15$ mm), - of a width of 8,5 mm or more but not more than 9,5 mm ($+0,05$ mm / - 0,09 mm), - of a thickness of 5,5 mm or more but not more than 5,8 mm ($+0/- 0,2$ mm), and - of a weight of 6,1 g or more but not more than 8,3 g 						
ex 8505 19 90	60	1502200/2018 PROLONG 2024	0562M	<p>NL(28.03.2023) request for amendment:</p> <p>Articles of agglomerated ferrite in the shape of arched rectangles, whether or not with rounded corners, with:</p> <ul style="list-style-type: none"> - a length of 9 mm or more but not more than 101 mm, - a width of 9 mm or more but not more than 101 mm, - a thickness of 1,85 mm or more but not more than 15,15 mm, <p>intended to become permanent magnets after magnetisation</p> <p>---</p> <p>Current text:</p> <p>Articles of agglomerated ferrite in the shape of a half-sleeve or a quarter-sleeve, or with rounded corners, to intended to become permanent magnet after magnetisation with the following dimensions:</p> <ul style="list-style-type: none"> - a length of 10 mm or more but not more than 100 mm (± 1 mm), - a width of 10 mm or more but not more than 100 mm (± 1 mm), 	S	Amendment	UNDER EXAMINATION	FR	Applicant	<p>Round 2024-07: request for amendment.//</p> <p>Intended use of the imported product: After import the magnets are either glued with epoxy glue or assembled with metal staples in the steel frame of the wiper system motor.</p>

				- a thickness of 2 mm or more but not more than 15 mm ($\pm 0,15$ mm)						
ex 8507 60 00	18	4793865/2018	0512B	<p>DE(12.09.2023) new proposal: Lithium-ion polymer accumulatorpack equipped with a battery management system and can-bus interface with:</p> <ul style="list-style-type: none"> - 6 modules with 90 cells or more but not more than 192 cells - a nominal voltage of 280 V or more but not more than 400 V, - a nominal capacity of 9,7 Ah or more but not more than 120 Ah, - a charging voltage of 110 V or more but not more than 495 V, and <p>in a metal casing with:</p> <ul style="list-style-type: none"> - a length of not more than 1 723 mm, - a width of not more than 1 162,23 mm, - a height of not more than 395 mm, <p>for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703</p> <p>---</p> <p>Current text: Lithium-ion polymer accumulator equipped with a battery management system and can-bus interface with:</p> <ul style="list-style-type: none"> - a length of not more than 1600 mm, - a width of not more than 448 mm, - a height of not more than 395 mm, - a nominal voltage of 280 V or more but not more than 400 V, 	S	Amendment	UNDER EXAMINATION	SE EU	Applicant Opposed	Round 2024-07 - request for amendment. For batteries

				- -a capacity of not more than 1860 mAh						
ex 8507 60 00	50	323555/2012	0507B	<p>DE + SK (12.09.2023) new proposal: Modules for the assembly of lithium-ion battery packs, with:</p> <ul style="list-style-type: none"> - a length of 298 mm or more, but not more than 500 mm, - a width of 33,5 mm or more, but not more than 209 mm, - a height of 75 mm or more, but not more than 228 mm, - a weight of 3,6 kg or more, but not more than 17 kg, and - a power of 458 Wh or more, but not more than 3 510 Wh <p>---</p> <p>Current text: Modules for the assembly of batteries of ion lithium electric accumulators with:</p> <ul style="list-style-type: none"> - a length of 298 mm or more, but not more than 500 mm, - a width of 33,5 mm or more, but not more than 209 mm, - a height of 75 mm or more, but not more than 228 mm, - a weight of 3,6 kg or more, but not more than 17 kg, and - a power of 458 Wh or more, but not more than 2 900 Wh 	S	Amendment	UNDER EXAMINATION	FR DE EU EU EU	Applicant Co-applicant Opposed Opposed Opposed	Round 2024-07- request for amendment.// Modules intended for the assembly of a rechargeable battery for the supply of power to electric motor vehicles
ex 8507 60 00	83	5691842/2021	0505B	<p>DE(12.09.2023) request for amendment: Modules for the assembly of ion lithium electric accumulators with:</p> <ul style="list-style-type: none"> - a length of 570 mm or more, but not more than 610 mm, - -a width of 210 mm or more, but not more than 240 mm, 	S	Amendment	UNDER EXAMINATION	DE EU EU EU	Applicant Opposed Opposed Opposed	Round 2024-01 - request for amendment. Battery modules for manufacturing drive batteries for electric or hybrid vehicles of chapters 8703 and 8704.

				<ul style="list-style-type: none"> - a height of 100 mm or more, but not more than 120 mm, - a weight of 28 kg or more, but not more than 35 kg, and - a capacity of not more than 2500 Ah and a nominal energy of less than 8,4 kW, <p>for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60</p> <p>---</p> <p>Current text: Modules for the assembly of ion lithium electric accumulators with:</p> <ul style="list-style-type: none"> - a length of 570 mm or more, but not more than 610 mm, - a width of 210 mm or more, but not more than 240 mm, - a height of 100 mm or more, but not more than 120 mm, - a weight of 28 kg or more, but not more than 35 kg, and - a capacity of not more than 2500 Ah and a nominal energy of less than 7,5 kW, <p>for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60</p> <p>(2)</p>						
ex 8507 90 80	20	2207294/2022	0517B	<p>DE(12.09.2023) request for amendment: Top cap or housing made of aluminium or ferrous alloy or stainless steel:</p> <ul style="list-style-type: none"> - whether or not including parts made of aluminum and aluminum alloy, - with or without sealing elements or other elements made of polymer material, 	S	Amendment	UNDER EXAMINATION	TR EU EU	Applicant Opposed Opposed	Round 2024/1 - Request for amendment.// for use in the manufacture of lithium-ion batteries

				<ul style="list-style-type: none"> - with or without a "current interrupt device " and an "evacuation valve" - with or without plastic sockets - with an outer diameter of 17 mm or more, but not more than 18 mm, <p>or rectangular with:</p> <ul style="list-style-type: none"> - length not greater than 450 mm, - width not greater than 200 mm, and - hight not greater than 150 mm, <p>for use in the manufacture of lithium-ion batteries (2)</p> <p>---</p> <p>Current text: Top cap made of ferrous alloy or stainless steel:</p> <ul style="list-style-type: none"> - whether or not including parts made of aluminum and aluminum alloy, - with sealing elements or other elements made of polymer material, - with a "current interrupt device " and an "evacuation valve", - with an outer diameter of 17 mm or more, but not more than 18 mm, <p>for use in the manufacture of lithium-ion batteries (2)</p>					
--	--	--	--	---	--	--	--	--	--

(1) A surveillance of imports of goods covered by this tariff suspension shall be established in accordance with the procedure laid down in Articles 55 and 56 of Commission Implementing Regulation (EU) 2015/2447 of 24 November 2015 laying down detailed rules for implementing certain provisions of Regulation (EU) No 952/2013 of the European Parliament and of the Council laying down the Union Customs Code (OJ L 343, 29.12.2015, p. 558).

(2) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.'

DISCLAIMER: The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group. Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic.

